

CSP DOT Series Specification


# PD80

## 24V-8mm



## 【General description】

- Color consistency SDCM<3(IP20),SDCM<5(IP67)
- Max.180° beam angle light-emitting
- Free connecting by soldering-free connectors
- Reel to reel production,few or no soldering joints
- 5 years warranty for indoor and outdoor.



## 【Dimension】

Input voltage: DC24V

CRI: 90

Max.power: 5.3W(1m)

Power range: 4.3-5.3W(1m)

Rated current: 0.2A(1m)

Typical Power: 4.8W(1m)

tape IP: IP20/IP65/IP67

On-off times: 10000 (test times)

Warranty: 5years


Cutting unit 100mm(3.93")

LED pitch: /


Min. bend diameter:  $\Phi$ 60mm(2.36")

Mounting: 3M tape

Copper foil: 2oz



Photometric of 1M strip




AAI Figurestrip

## 【Photo-electric Parameters】






CRI	Color	CCT	Lumen(lm/m)	Lumen(lm/ft)	lm/W	ErP 2019
Ra>90	SW	2700K	395	120	82	G
Ra>90	WW	3000K	400	122	83	G
Ra>90	NW	4000K	410	125	85	G
Ra>90	W	6500K	385	117	80	G

- 1.The tolerance of output data can be vary up to 15%.
- 2.the output data tested according to IES TM-30-15.
- 3.the output data is based on IP20/lmerter, data of 5m in only for reference.
- 4.IP protection process leads changes to size, CCT and luminous flux.












## 【IP process information】



## 【Electronic & output data】


IP Process	Picture	Picture description	Size	optional CCT/color for finished product	lumen output rate
NO		No proof	8mm*1.7mm	2700K/3000K/4000K/6500K	100%
NA		Nano-proof	8mm*1.8mm	2700K/3000K/4000K/6500K	98%
ES		Extrusion tube	11mm*5.0mm	2700K/3000K/4000K/6500K	90%
ET		Extrusion tube	10mm*5.0mm	2700K/3000K/4000K/6500K	88%
EF		Extrusion filing	10mm*5.0mm	2700K/3000K/4000K/6500K	88%

## 【Accessories Information】


Name	Picture	Code	coding	description
Fixed Clip		94-02-00-0002	FSW08SA	Silicone clip, screw: PA 3*8mm, suitable for 8mm FPC,EF/ET strip
Silicone Plug Kit		94-02-00-0044	DT08EA-A	Silicone plug kit, suitable for 8mm board width, ET/EF series silicone extrusion light strip
Silicone stopper kit		94-02-00-0045	DW08EA-A	Silicone tail plug kit, suitable for 8mm board width, ET/EF series silicone extrusion light strip
Mounting groove		94-02-00-0024	CVT08EA-12100100	Transparent PVC mounting groove,suitable for 8mm FPC,silicone extruded EF/ET strip
Stopper glue		94-16-03010001	AS-PG-0003	Silicone gel,suitable for ET/EF/EG waterproof LED strip
ET solderless plug		94-03-00-0027	PT208-ETWA	Monochromatic light strip, 8mm board width, ET protection technology
ET press-fit terminals		94-03-00-0028	CBX208-ETWA020	Monochromatic light strip, 8mm board width, ET protection technology
ET press-fit terminal kit		94-03-00-0029	STBX208-ETWA020	Monochromatic light strip, 8mm board width, ET protection technology
Connector for wire and FPC		/	CXB208-DFTA	2PIN,wire to board(without wire),suitable for 8mm single color IP20 strips
Connector for FPC and FPC		/	CBB208-DFTA	2PIN,board to board,suitable for 8mm single color IP20 strips
L-connector for FPC and FPC		/	CBBL208-DFTA	2PIN,board to board(L shape),suitable for 8mm single color IP20 strips

## 【Packing】

Colors brand package




General customized package



IP Process	Product size(mm)	Product quantity (m/reel)	Product quantity (m/case)	Product net weight(kg)	Net weight per box(kg)	Gross weight(kg)	Package size (mm)
NO	5000*8*1.7	5	300	0.11	6.6	7.6	410*410*260
NA	5000*8*1.8	5	300	0.115	6.9	7.935	410*410*260
ET	5000*10*5.0	5	200	0.42	16.9	19.3	410*410*260
ES	5000*11*5.0	5	200	0.45	18.0	20.4	410*410*260
EF	5000*10*5.0	5	200	0.47	18.8	21.2	410*410*260


Remark: data with 10% tolerance

### · Engineering packaging of NO(IP20).



### · Engineering packaging

(free-soldering end caps with 40 cover per box could be ordered separately if needed)



IP Process	Product size(mm)	Product quantity (m/reel)	Product quantity (m/case)	Product net weight(kg)	Net weight per box(kg)	Gross weight(kg)	Package size (mm)
NO	50000*8*1.7	50	650	0.92	12.1	13	410*410*260
NA	50000*8*1.8	50	650	0.97	12.6	13.6	410*410*260
ET	50000*10*5.0	50	100	4.5	8.5	13	255*255*260
ES	50000*11*5.0	50	100	4.8	8.5	13.3	255*255*260
EF	50000*10*5.0	50	100	4.9	8.5	13.4	255*255*260

Remark: data with 10% tolerance

### **【Precautions】**

- Please drive the led strip with 24VDC isolated power, and the ripple of the constant voltage source should be less than 5%.
- Please do not bend the strip into an arc with a diameter less than 60mm to ensure the longevity and reliability.
- Do not fold it in case any damage of LED beads.
- Do not pull the power wire hard to ensure the longevity. Any Crash may damage the LED light is prohibited.
- Please make sure the wire is connected to the anode and cathode correctly. The power output should be consistent with the voltage of the strip to avoid damage.
- LED lights should be stored in dry, sealed environment. Please only unpack it before usage. Ambient temperature: -25°C-40°C. Storage temperature: 0°C-60°C. Please use the strips without waterproof within indoor environment with humidity less than 70%.
- Please be careful during operation. Do not touch the AC power supply in case of electric shock.
- Please leave at least 20% power for the power supply during using to ensure there is enough power supply to drive the product.
- Do not use any acid or alkaline adhesives to fix the product (e.g.: glass cement).
- Do not scratch the product when IP process of the product is NA. Ultraviolet rays will damage the nano-layers on the product and seriously affect the life of the product.